



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS # : 30236

MARINE FUELS

Date of the previous version: 2019-12-13

Revision Date: 2020-06-08

Version 4.01

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	MARINE FUELS
REACH registration No	01-2119474894-22-0100
Other names	MARINE RESIDUAL FUELS - IFO, Fuel from 30cst to 700 cst, Fuel HS, Fuel LS VLSFO: Very Low Sulfur Fuel Oil, Bunker Fuel
Substance/mixture	Substance

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Fuel used in marine applications : diesel engines and boilers.

1.3. Details of the supplier of the safety data sheet

Supplier	TOTAL MARINE FUELS GLOBAL SOLUTIONS 182 Cecil Street #27-01 Frasers Tower Singapore 069547 Tel : +65 6849 5266 Fax : +65 6337 9483
-----------------	---

For further information, please contact:

Contact Point	HSE
E-mail Address	rm.mkefr-fds@total.com

1.4. Emergency telephone number

Emergency telephone: +44 1235 239670

See section 16 for additional information

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008

For the full text of the H-Statements mentioned in this Section, see Section 2.2.

Acute inhalation toxicity - vapor - Category 4 - (H332)
Carcinogenicity - Category 1B - (H350)



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

Reproductive toxicity - Category 2 - (H361d)
 Specific target organ toxicity (repeated exposure) - Category 2 - (H373)
 Acute aquatic toxicity - Category 1 - (H400)
 Chronic aquatic toxicity - Category 1 - (H410)

2.2. Label elements

Labelled according to REGULATION (EC) No 1272/2008

Contains Fuel oil, residual



Signal word
 DANGER

Hazard Statements

H350 - May cause cancer
 H332 - Harmful if inhaled
 H361d - Suspected of damaging the unborn child
 H373 - May cause damage to organs through prolonged or repeated exposure in contact with skin
 H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements

P201 - Obtain special instructions before use
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray
 P280 - Wear protective gloves/protective clothing/eye protection/face protection
 P308 + P313 - IF exposed or concerned: Get medical advice/attention
 P331 - Do NOT induce vomiting
 P273 - Avoid release to the environment
 P501 - Dispose of contents/container to industrial incineration plant

Supplemental Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking
 Restricted to professional users

2.3. Other hazards

Physical-Chemical Properties

In the presence of hot spots, there is a special risk of fire or explosion under certain conditions involving accidental release of vapor or leaks of product under pressure.

Properties Affecting Health

Contact with hot product will cause thermal burns.
 Vapors or mists are irritating for mucous membranes, notably in the eyes.
 Hydrogen sulphide can accumulate in the head space of storage tanks containing this product and can reach potentially hazardous concentrations.



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Chemical nature

A complex and variable combination of paraffinic, cyclic and aromatic hydrocarbons having a carbon number range predominantly of C15 to C50 and boiling in the range of approximately 150°C to 750°C. They may contain sulphurated derivatives and organic acids. This product contains polycyclic aromatic hydrocarbons (PAH), some of which are considered carcinogens.

Chemical Name	EC-No	REACH registration No	CAS-No	Weight %	Classification (Reg. 1272/2008)
Fuel oil, residual	270-675-6	01-2119474894-22	68476-33-5	>99	Carc. 1B (H350) Repr. 2 (H361d) Acute Tox. 4 (H332) STOT RE 2 (H373) Aquatic Acute 1 (H400) Aquatic chronic 1 (H410)

Additional information

Hydrogen sulphide can accumulate in the head space of storage tanks containing this product and can reach potentially hazardous concentrations.

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

If there is any suspicion of inhalation of H₂S. Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures.

Eye contact

Rinse thoroughly with plenty of water, also under the eyelids.

Check for and remove any contact lenses. Rinse eyes.

In case of contact with the hot product, COOL THE EYE IMMEDIATELY AND COPIOUSLY WITH COLD WATER for 10 minutes, keeping the eye open if possible. Take the person to a specialised medical centre.

Skin contact

Immediately remove all stained or splashed clothing that is not adhering to the skin.

Remove as much as possible by wiping. If necessary, use a fatty substance of animal or vegetable origin. Never use gasoline, kerosene or other solvents for washing of contaminated skin.

Wash affected area with soap and water. Seek medical attention if skin irritation, swelling or redness develops and persists.

High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent. In this case, the casualty should be sent immediately to hospital.

For minor thermal burns. Do not remove clothing if adhering to skin. Hold the burned area under cold running water for at least five minutes, or until the pain subsides. Seek medical attention in all cases of serious burns.

Inhalation

Inhalation is unlikely because of the low vapour pressure of the substance at ambient



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

temperature. Exposure to vapours may however occur when the substance is handled at high temperatures with poor ventilation. In case of exposure to intense concentrations of vapours, fumes or spray, transport the person away from the contaminated zone, keep warm and allow to rest. Immediately begin artificial respiration if breathing has ceased. Call a physician immediately.

If there is any suspicion of inhalation of H₂S. Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. If not breathing, give artificial respiration. Provision of oxygen may help. Remove casualty to fresh air as quickly as possible. Obtain medical advice for further treatment.

Ingestion Do NOT induce vomiting. Give nothing to drink. Never give anything by mouth to an unconscious person.
Consult a physician.

Protection of First-aiders CAUTION! First aid personnel must be aware of personal risk during rescue!.
Use personal protective equipment. See Section 8 for more detail.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact Burning feeling and temporary redness. Risk of burns (if the product is hot).

Skin contact Prolonged or repeated contact may dry skin and cause irritation. Risk of burns (if the product is hot).

Inhalation Inhalation of vapors in high concentration may cause irritation of respiratory system. Causes headache, drowsiness or other effects to the central nervous system. Risk of hydrogen sulphide intoxication (H₂S).

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician In the case of thermal burns. DO NOT attempt to remove portions of clothing glued to burnt skin but cut round them. Treat symptomatically.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media Extinguishing media - large fires: Foam (specifically trained person only). Water fog (trained personnel only).
Extinguishing media - small fires: Carbon dioxide (CO₂). Dry powder. Sand or earth. Other inert gases (subject to regulations).

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.
Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

5.2. Special hazards arising from the substance or mixture

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

If sulphur compounds are present in appreciable amounts, combustion products may include also H₂S and SO_x (sulfur oxides) or sulfuric acid.

5.3. Advice for fire-fighters

Special protective equipment for fire-fighters

In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Other information

Cool down any tanks and surfaces exposed to fire by spraying abundantly with water. Use water to cool tanks and parts exposed to the thermal flux not caught up in the flames. Cool containers / tanks with water spray.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information

Except in case of small spillages, The feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

If required, notify relevant authorities according to all applicable regulations.

When the presence of dangerous amounts of H₂S around the spilled product is suspected or proved. additional or special actions may be warranted to determine controls appropriate to local circumstances.

Evacuate non-essential personnel. Avoid direct contact with released material. Stop or contain leak at the source, if safe to do so.

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Ensure adequate ventilation, especially in confined areas.

For personal protection see section 8.

Advice for non-emergency personnel

Do not touch or walk through spilled material. Evacuate personnel to safe areas. Ensure adequate ventilation. For personal protection see section 8.

Advice for emergency responders

In case of:

Small spillages: normal antistatic working clothes are usually adequate.

Large spillages: full body suit of chemically resistant and antistatic material. Work gloves (preferably gauntlets) providing adequate chemical resistance. Remarks:.. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

Work helmet. Antistatic non-skid safety shoes or boots. if necessary heat-resistant.

Goggles and/or face shield, if splashes or contact with eyes is possible or anticipated.

Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (and when applicable: for H₂S). If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

6.2. Environmental precautions

General Information

The product should not be allowed to enter drains, water courses or the soil. Solidified product may clog drains and sewers. If necessary, Consult an expert. Local authorities should be advised if significant spillages cannot be contained.



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

6.3. Methods and material for containment and cleaning up

Methods for containment

Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13). Ensure adequate ventilation, especially in confined areas. Large spillages may be cautiously covered with foam, if available, to limit fire risk.

Methods for cleaning up

Let hot product cool down naturally. Collect free product with suitable means. Use mechanical means such as pumps, skimmers and absorbent materials. Pick up and transfer to properly labeled containers. Cleaning with high pressure washers. or. Wash off with warm water. Wear respiratory protection.

In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations. Transfer recovered product and other materials to suitable tanks or containers and store/dispose according to relevant regulations.

In case of spillage in the water:

Product less dense than water. In case of small spillages in closed waters . contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. control the spreading of the spillage.

If possible, large spillages in open waters should be contained with floating barriers or other mechanical means, collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities. Collect recovered product and other materials in suitable tanks or containers for recovery or safe disposal.

Product which is denser than water will sink to the bottom, and usually no intervention will be feasible. If possible, collect the product and contaminated materials with mechanical means, and store/dispose of according to relevant regulations. In special situations (to be assessed on case-by case basis, according to expert judgement and local conditions), excavations of trenches on the bottom to collect the product, or burying the product with sand may be a feasible option.

6.4. Reference to other sections

Personal Protective Equipment

See Section 8 for more detail.

Waste treatment

See section 13.

Other information

Recommended measures are based on the most likely spillage scenarios for this material. However, local conditions (wind, air temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken.

Concentration of H₂S in tank headspaces may reach hazardous values, especially in case of prolonged storage. This situation is especially relevant for those operations which involve direct exposure to the vapours in the tank. Spillages of limited amounts of products, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which presumably do not entail exposure to dangerous concentrations:

As H₂S has a density greater than ambient air, a possible exception may regard the build-up of dangerous concentrations in specific spots, like trenches, depressions or confined spaces. In all these circumstances, however, the correct actions should be assessed on a case-by-case basis.

Section 7: HANDLING AND STORAGE



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

7.1. Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Hydrogen sulphide can accumulate in the head space of storage tanks containing this product and can reach potentially hazardous concentrations. Wear personal protective equipment. Refer to Section 8.

Take precautionary measures against static electricity.

The inspection, cleaning and maintenance of storage containers require the application of strict procedures and must be entrusted to qualified personnel (internal or external).

Avoid splash filling of bulk volumes when handling hot liquid product. Keep the temperature of the product as low as possible to minimise the release of fumes. Never check the tank level by using a naked flame.

Do not smoke. Avoid breathing vapors or mists. Ensure adequate ventilation. Vapors may form explosive mixtures with air.

Avoid contact with skin, eyes and clothing. Wear suitable protective clothing.

Do not use compressed air for filling, discharging, or handling operations.

Technical measures

Ensure adequate ventilation.

Do not use compressed air for filling, discharging, or handling operations.

Design installations to avoid spills and splashes of hot product. Take all necessary precautions to prevent water from entering the containers, tanks, transfer lines etc...

Prevention of fire and explosion

Handle away from any source of ignition (open flame and sparks) and heat (hot manifolds or casings). Take precautionary measures against static discharges. Do not heat the pumps or pipes using an open flame. Ground/bond containers, tanks and transfer/receiving equipment. Never weld any container or empty pipe that has not been degassed.

Do not use compressed air for filling, discharging or handling. OPERATE ONLY ON COLD AND DEGASSED TANKS IN VENTILATED PREMISES (TO AVOID RISK OF EXPLOSION).

Hygiene measures

Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes and clothing.

Change contaminated clothes at the end of working shift. Wash hands before breaks and immediately after handling the product.

Provide regular cleaning of equipment, work area and clothing.

IF ON SKIN: Wash skin with soap and water: Remove as much as possible by wiping. If small amount of product only comes into contact with the skin, remove with vegetable oil. White oil, lukewarm paraffin or a suitable soap recommended for this purpose may also be used. Do not use abrasives, solvents or fuels.

Do not put product contaminated rags into workwear pockets.

Gloves must be periodically inspected and changed in case of wear, perforations or contaminations.

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Use personal protective equipment as required.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Lines used for the product and pump devices are to be insulated and equipped with a heating device.

. Storage installations should be designed with adequate bunds so as to prevent ground or water pollution in case of leaks or spills.

. Before entering storage tanks and commencing any operation in a confined area, check the atmosphere for oxygen content and flammability. If sulphur compounds are suspected

SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

to be present in the product, check the atmosphere for H₂S content.
 . Take precautionary measures against static discharges. Ensure all equipment is electrically grounded before beginning transfer operations. Store the packed products (drums, samples, cans ...) in properly ventilated rooms, away from damp, heat and any potential source of ignition. Do not weld, solder, drill, cut or incinerate empty containers, unless they have been properly cleaned. Empty containers may contain combustible product residues.
 . Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Keep containers tightly closed and properly labelled. Do not remove the hazard labels of the containers (even if they are empty).
 . Store separately from oxidising agents.
 . Store in accordance with the particular national regulations. Keep away from food, drink and animal feedingstuffs.

Materials to Avoid

Strong oxidizing agents.

Packaging material

Use only containers, seals, pipes, etc... made in a material suitable for use with aromatic hydrocarbons. heat resistant. Recommended materials for containers, or container linings use mild steel, stainless steel. Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Compatibility should be checked with the manufacturer.

7.3. Specific end uses

Specific use(s) See exposure scenarios.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits Hydrogen sulphide (EU): OEL = 7 mg/m³, 5ppm (8 h), 14 mg/m³, 10ppm (short-time)

Other constituents required for disclosure

Legend See section 16

DNEL Worker (Industrial/Professional)

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Fuel oil, residual 68476-33-5	4716.8 mg/m ³ (Inhalation)		0.18 mg/m ³ (Inhalation)	0.065 mg/kg/8h (dermal)

DNEL Consumer

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Fuel oil, residual 68476-33-5			0.015 mg/kg/24h (oral)	

Predicted No Effect Concentration (PNEC)

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
Fuel oil, residual 68476-33-5						66.7 mg/kg food



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

8.2. Exposure controls

Occupational Exposure Controls

Engineering Measures

Ensure adequate ventilation. Do not enter empty storage tanks until measurements of available oxygen have been carried out. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Personal Protective Equipment

General Information

Protective engineering solutions should be implemented and in use before personal protective equipment is considered.
Use personal protective equipment in good condition.

Respiratory protection

To enter tankers, tanks, reservoirs where the oxygen content is too low, wear insulating respiratory apparatus.
. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.
. In an emergency or for exceptional short-lasting jobs in an atmosphere polluted by the product, it is necessary to wear protective respiratory equipment.
. Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H₂S) or self-contained breathing apparatus (SCBA). (EN 529).

Eye Protection

Work helmet with face shield and neck cloth (full head protection). Tightly fitting safety goggles. or. Face-shield.

Skin and body protection

Wear single use overall. Hydrocarbon resistant clothing. Protective shoes or boots. Rubber or plastic boots. Coverall (with trousers legs over boots).

Hand Protection

Hydrocarbon-proof gloves. Nitrile rubber. Neoprene gloves.
. Wear suitable gloves tested to EN374.
. Gloves anti-heat for the liquefied product (EN 407, level 1).
. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use.

Environmental exposure controls

General Information

The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance

viscous

Color

brown dark green or dark brown black

Physical State @20°C

viscous



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

Other relevant operational conditions of use		liquid @ > 50 °C	
Odor		Hydrocarbon-like	
Odor Threshold		No information available	
Property	Values	Remarks	Method
pH		Not applicable	
Melting point/range		No information available	
Boiling point/boiling range	160 - 750 °C 320 - 1382 °F		EN 15199 EN 15199
Flash point	> 60 °C > 140 °F		ASTM D 93 ASTM D 93
Evaporation rate		Not applicable	
Flammability Limits in Air			
upper	5 %		
Lower	0.5 %		
Vapor Pressure	< 1 kPa @ 150 °C		EN 13016-1
Vapor Pressure			
Vapor density	> 5		
Relative density		No information available	
Density	840 - 1100 kg/m ³	@ 15 °C	
Water solubility		Not applicable	
Solubility in other solvents		Soluble in many common organic solvents	
logPow		Not applicable	
Autoignition temperature	> 380 °C > 716 °F		DIN 51794 DIN 51794
Decomposition temperature		No information available	
Viscosity, kinematic	> 20.5 mm ² /s 30 - 700 mm ² /s > 3 mm ² /s	@ 40 °C @ 50 °C @ 100 °C	ISO 3104 ISO 3104 ISO 3104
Explosive properties	Not considered explosive based on chemical structure and oxygen balance considerations		
Oxidizing Properties	This product is not considered oxidising based on chemical structure considerations		
Possibility of hazardous reactions	None under normal processing		

9.2. Other information**Freezing Point** No information available**Pour point** < 30 °C**Section 10: STABILITY AND REACTIVITY**10.1. Reactivity**General Information** No information available.10.2. Chemical stability



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Take precautionary measures against static discharges. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Materials to Avoid Strong oxidizing agents. Strong acids. Halogens.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products None under normal use.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact This product does not meet the EU criteria for classification. Prolonged or repeated contact may dry skin and cause irritation. Risk of burns (if the product is hot).

Eye contact This product does not meet the EU criteria for classification. Burning feeling and temporary redness. Risk of burns (if the product is hot).

Inhalation . Inhalation of vapors in high concentration may cause irritation of respiratory system. Causes headache, drowsiness or other effects to the central nervous system. Risk of hydrogen sulphide intoxication (H₂S).

Ingestion . Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Fuel oil, residual	LD50 5270 mg/kg bw (rat - OECD 401)	LD50 > 2000 mg/kg bw (rabbit - OECD 434)	LC50(4h) 4.1 mg/l (males - aerosol - rat) LC50(4h) 4.5 mg/l (females - aerosol - rat)

Sensitization

Sensitization This product does not meet the EU criteria for classification.

Specific effects



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

Carcinogenicity Positive results obtained from mouse skin painting studies and from an initiation/promotion assay indicate that these components are carcinogenic.

Chemical Name	European Union
Fuel oil, residual 68476-33-5	Carc. 1B (H350)

Mutagenicity The mutagenic potential of the substance has been extensively studied in a range of in-vivo and in-vitro assays. The majority of the studies showed no evidence of mutagenic activity.

Germ Cell Mutagenicity The weight of evidence from in vivo and in vitro mutagenic studies indicates that this substance does not meet the criteria for classification under regulation.

Reproductive toxicity Suspected of damaging the unborn child.

Developmental Toxicity The available data indicate that these components adversely affect foetal development.

Chemical Name	European Union
Fuel oil, residual 68476-33-5	Repr. 2 (H361d)

Repeated dose toxicity

Target Organ Effects (STOT)

Specific target organ systemic toxicity (single exposure) This product does not meet the EU criteria for classification.

Specific target organ systemic toxicity (repeated exposure) Causes damage to organs through prolonged or repeated exposure. Repeated exposure may cause skin dryness or cracking.

Other information

Other information Not relevant.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Fuel oil, residual 68476-33-5	EL50(72h) 0.32 mg/l (Pseudokirchnerella subcapitata - OECD 201)	EL50(48h) 0.22 mg/l (Daphnia magna - OECD 202)	LL50 (96h) 79 mg/l (Oncorhynchus mykiss - OECD 203)	

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Fuel oil, residual 68476-33-5		NOEL (21d) 0.27 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) 0.1 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	

Effects on terrestrial organisms

No information available.

12.2. Persistence and degradability

General Information

Standard tests for this parameter are not appropriate

12.3. Bioaccumulative potential

Product Information

Standard tests for this parameter are not appropriate.

logPow

Not applicable

Component Information

No information available.

12.4. Mobility in soil

Mobility				
Method	Compartment	Result	(%)	Remarks
Percent distribution in media (Calculation according to Mackay, Level III)	Soil		67.81	
Percent distribution in media (Calculation according to Mackay, Level III)	Sediment		27.63	
Percent distribution in media (Calculation according to Mackay, Level III)	Air		4.55	
Percent distribution in media (Calculation according to Mackay, Level III)	Water		0.01	

Soil

Given its physical and chemical characteristics, the product generally shows low soil mobility.

Air

Loss by evaporation is limited.

Water

The product floats or settles, depending on its density.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

This product contains no substance considered as PBT and/or vPvB according to REACH regulation annex XIII criteria.

12.6. Other adverse effects

General Information

No information available.



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products	Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of contents/ container to an approved incineration plant.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
EWC Waste Disposal No.	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

Section 14: TRANSPORT INFORMATION

Note if transported at ambient temperature, This dangerous good could also be transported under UN code 3082

ADR/RID

UN/ID No	UN3256
Proper shipping name	ELEVATED TEMPERATURE LIQUID, FLAMMABLE, N.O.S.
Hazard class	3
Packing Group	III
ADR/RID-Labels	3
Environmental hazard	Yes
Classification Code	F2
Special Provisions	274, 560
Tunnel Restriction Code	(D/E)
ADR Hazard Id (Kemmler Number)	30
Description	UN3256, ELEVATED TEMPERATURE LIQUID, FLAMMABLE, N.O.S. (Fuel oil, residual), 3, III, (D/E), Environmentally hazardous
Excepted Quantity	E0
Limited quantity	0

IMDG/IMO

UN/ID No	UN3256
Proper shipping name	ELEVATED TEMPERATURE LIQUID, FLAMMABLE, N.O.S.
Hazard class	3
Packing Group	III
Marine pollutant	Yes
EmS No.	F-E, S-D
Description	UN3256, ELEVATED TEMPERATURE LIQUID, FLAMMABLE, N.O.S. (FUEL OIL, RESIDUAL), 3, III, MARINE POLLUTANT
Special Provisions	274
Excepted Quantity	E0
Limited quantity	0

ICAO/IATA

Description Forbidden BY PASSENGER AIR

Forbidden



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

ADN

UN/ID No	UN3256
Proper shipping name	ELEVATED TEMPERATURE LIQUID, FLAMMABLE, N.O.S.
Hazard class	3
Hazard Labels	3
Packing Group	III
Environmental hazard	Yes
Classification Code	F2
Special Provisions	274, 560
Description	UN3256, ELEVATED TEMPERATURE LIQUID, FLAMMABLE, N.O.S. (Fuel oil, residual), 3, III, Environmentally hazardous
Excepted Quantity	E0
Limited quantity	0
Ventilation	VE01
Equipment Requirements	PP, EX, A

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

REACH

This mixture contains only ingredients which have been registered, or are exempt from registration, according to Regulation (EC) No. 1907/2006 (REACH).

RESTRICTIONS - REACH TITLE VIII ANNEX XVII - REGULATION (EC) N ° 1907/2006 - restrictions not applicable to the use of this product mentioned in the msds

Other regulations

Directive 2004/37/EC of the European Parliament and of the Council of 29 April 2004 on the protection of workers from the risks related to exposure to carcinogens or mutagens at work Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers. Take note of Dir 94/33/EC on the protection of young people at work.

International Inventories All the substances contained in this product are listed or exempted from listing in the following inventories:
Europe (EINECS/ELINCS/NLP)

Further information

No information available

15.2. Chemical Safety Assessment

Chemical Safety Assessment See exposure scenarios



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

Section 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H332 - Harmful if inhaled

H350 - May cause cancer in contact with skin

H361d - Suspected of damaging the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure in contact with skin

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

ATE = Acute Toxicity Estimate

QSAR = Quantitative Structure-Activity Relationship

EL50 = median Effective Loading

NOELR = No Observed Effect Loading Rate

PAH = Polycyclic aromatic hydrocarbons

LOEC = Lowest Observed Effect Concentration

PVA = Polyvinyl alcohol

PVC = Polyvinyl chloride

ECOSAR = Ecological Structure Activity Relationships

CNS = Central nervous system

EPA = Environmental Protection Agency

ErL50 = effective loading on growth rate in algae test, to cause a 50% response

EbL50 = effective loading on growth with the control in algae test, to cause a 50% response

DNEL = Derived No Effect Level

PNEC = Predicted No Effect Concentration

dw = dry weight

fw = fresh water

mw = marine water

or = occasional release

Legend Section 8

OEL = Occupational Exposure Limit

TWA: Time Weight Average

STEL: Short Time Exposure Limit

PEL: Permissible exposure limit



SDS # : 30236

MARINE FUELS

Revision Date: 2020-06-08

Version 4.01

REL: Recommended exposure limit

TLV: Threshold Limit Values

+	Sensitizer	*	Skin designation
**	Hazard Designation	C:	Carcinogen
M:	Mutagen	R:	Toxic to reproduction

Revision Date: 2020-06-08
Revision Note (M)SDS sections updated: 14.

Further information Other uses than these listed under section 1.2 may have been foreseen for the substance(s) contained in the product. Please contact us if your use is not listed under section 1.2.

Emergency telephone numbers

FRANCE:

ORFILA Tél : 01.45.42.59.59

PARIS : Hôpital Fernand Widal 200, rue du Faubourg Saint-Denis 75475 Paris Cédex 10 ,

Tel : 01.40.05.48.48. - MARSEILLE : Hopital Salvator, 249 bd Ste Marguerite 13274

Marseille cedex 5, Tel : 04.91.75.25.25. - LYON : Hopital Hédouard Herriot, 5 place

d'Arsonvil, 69437 Lyon cedex 3, Tel : 04.72.11.69.11. - NANCY : Hopital central, 29 Av du

Mal De Lattre de Tassigny, 54000 Nancy, Tel : 03.83.32.36.36 ou le SAMU : Tel (15)

UK:

01923 694000 - NHS Direct: 0845 46 47 / Textphone: 0845 606 46 47

GERMANY:

Giftnotruf Berlin, Tel. 0049 (0)30 19240 (24 h erreichbar, Beratung in Deutsch und

Englisch)

SPAIN:

NÚMERO DE EMERGENCIAS 24 HORAS 900 181 566

BELGIUM:

Poison center: c/o Hôpital Militaire Reine Astrid - Militair Hospitaal Koningin Astrid, 1 Rue

Bruyn - Bruynstraat 1, B-1120 Bruxelles - Brussel

+32 (0)70 245 245

NETHERLAND:

+ 31 (0) 800 0996612

ITALY :

Centro Antiveleni Ospedale Niguarda Ca' Granda, Piazza Ospedale Maggiore 3

Milan 20162 , +39 02 6610 1029.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet

ES08004

Version 1.0

Trade name / designation Heavy Fuel Oil

1. Exposure scenario

Formulation & (re)packing of substances and mixtures, Industrial.

Use Descriptor

Sector of use

SU3 - Industrial Manufacturing (all)

SU10 - Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

Process category

PROC1 - Use in closed process, no likelihood of exposure

PROC2 - Use in closed, continuous process with occasional controlled exposure

PROC3 - Use in closed batch process (synthesis or formulation)

PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC15 - Use as laboratory reagent

Environmental Release Category

ERC2 - Formulation of preparations

Specific Environmental Release Category

ESVOC SpERC 2.2.v1.

Processes, tasks, activities covered

Formulation of the substance and its mixtures in batch or continuous operations within closed or contained systems, including incidental exposures during storage, materials transfers, mixing, maintenance, sampling and associated laboratory activities.

2. Operational conditions and risk management measures

2.1. Control of environmental exposure

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Fraction of EU tonnage used in region: 0.1

Regional use tonnage (tonnes/year): 1.1E+7

Fraction of Regional tonnage used locally: 2.6E-3

Annual site tonnage (tonnes/year): 3.0E+4

Maximum daily site tonnage (kg/day): 1.0+5

Frequency and duration of use Continuous release

Emission Days (days/year): 300

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Release fraction to air from process (initial release prior to RMM): 2.2E-3

Release fraction to wastewater from process (initial release prior to RMM): 5.0E-6

Release fraction to soil from process (initial release prior to RMM): 0.0001

Technical conditions and measures at process level to prevent release

Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Risk from environmental exposure is driven by humans via indirect exposure

If discharging to domestic sewage treatment plant, no onsite wastewater treatment required

Prevent discharge of undissolved substance to or recover from onsite wastewater

Treat air emission to provide a typical removal efficiency of (%): 0

Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): >=54

If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%): ≥ 0

Organizational measures to prevent/limit release from the site

Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Estimated substance removal from wastewater via domestic sewage treatment (%): 88.8

Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%): 88.8

Maximum allowable site tonnage (MSafe) (kg/d): $1.1E+5$

Assumed domestic sewage treatment plant flow (m³/d): 2000

Conditions and measures related to external treatment of waste for disposal

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Remarks

Additional information on the basis for the allocation of the identified OCs (operating conditions) and RMMs (Risk Management Measures) is contained in Petrorisk file

2.2. Control of exposure - Workers / Consumers

Product characteristics**Physical State**

Liquid, vapor pressure < 0.5 kPa at STP

Concentration of substance in product

Covers percentage substance in the product up to 100 % (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting exposure

Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.

2.2a. Control of worker exposure

Contributing Scenarios	Operational conditions and risk management measures
General measures (carcinogens)	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimize exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorized persons; provide specific activity training to operators to minimize exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure. Avoid carrying out activities involving exposure for more than 4 hours. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
General exposures (closed systems) Process sampling	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure. Avoid carrying out activities involving exposure for more than 15 minutes. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Bulk product storage	Store substance within a closed system. Avoid carrying out activities involving exposure for more than 4 hours. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimize exposure. Wear suitable gloves tested to EN374.
Marine vessel/barge (un)loading	Transfer via enclosed lines. Avoid carrying out activities involving exposure for more than 4 hours. Clear transfer lines prior to de-coupling. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Road tanker/rail car loading	Ensure material transfers are under containment or extract ventilation. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment break-in or maintenance. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Product sampling	Sample via a closed loop or other system to avoid exposure. Avoid carrying out operation for more than 15 minutes. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Drum/batch transfers	Ensure material transfers are under containment or extract ventilation. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or. Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

2.2b. Control of consumer exposure

Product Category(ies)	Operational conditions and risk management measures
Not applicable	

3. Exposure estimation and references

Health

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated

Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

4. Guidance for Downstream User to check compliance with the Exposure scenario

Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for carcinogenic effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Risk Management Measures are based on qualitative risk characterization.

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

ES08005

Version 1.0

Trade name / designation Heavy Fuel Oil

1. Exposure scenario

Uses in Coatings, Industrial.

Use Descriptor

Sector of use

SU3 - Industrial Manufacturing (all)

Process category

PROC1 - Use in closed process, no likelihood of exposure

PROC2 - Use in closed, continuous process with occasional controlled exposure

PROC3 - Use in closed batch process (synthesis or formulation)

PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC15 - Use as laboratory reagent

Environmental Release Category

ERC4 - Industrial use of processing aids in processes and products, not becoming part of articles

Specific Environmental Release Category

ESVOC SpERC 4.3a.v1.

Processes, tasks, activities covered

Covers the use in coatings (paints, inks, adhesives, etc) within closed or contained systems including incidental exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application activities and film formation) and equipment cleaning, maintenance and associated laboratory activities.

2. Operational conditions and risk management measures

2.1. Control of environmental exposure

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Fraction of EU tonnage used in region: 0.1

Regional use tonnage (tonnes/year): 1.0E+2

Fraction of Regional tonnage used locally: 1

Annual site tonnage (tonnes/year): 1.0E+2

Maximum daily site tonnage (kg/day): 5.0+3

Frequency and duration of use

Continuous release
Emission Days (days/year): 20

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Release fraction to air from process (initial release prior to RMM): 0.98

Release fraction to wastewater from process (initial release prior to RMM): 2.0E-5

Release fraction to soil from process (initial release prior to RMM): 0

Technical conditions and measures at process level to prevent release

Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Risk from environmental exposure is driven by humans via indirect exposure

No wastewater treatment required

Prevent discharge of undissolved substance to or recover from onsite wastewater

Treat air emission to provide a typical removal efficiency of (%): 90

Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 0

If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%): ≥ 0

Organizational measures to prevent/limit release from the site

Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Estimated substance removal from wastewater via domestic sewage treatment (%): 88.8

Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%): 88.8

Maximum allowable site tonnage (MSafe) (kg/d): $1.1E+5$

Assumed domestic sewage treatment plant flow (m³/d): 2000

Conditions and measures related to external treatment of waste for disposal

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Remarks

Additional information on the basis for the allocation of the identified OCs (operating conditions) and RMMs (Risk Management Measures) is contained in Petrorisk file

2.2. Control of exposure - Workers / Consumers

Product characteristics**Physical State**

Liquid, vapor pressure < 0.5 kPa at STP

Concentration of substance in product

Covers percentage substance in the product up to 100 % (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting exposure

Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.

2.2a. Control of worker exposure

Contributing Scenarios	Operational conditions and risk management measures
General measures (carcinogens)	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimize exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorized persons; provide specific activity training to operators to minimize exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
Film formation - force drying, stoving and other technologies	Provide extract ventilation to points where emissions occur. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
General exposures (closed systems)	Handle substance within a closed system. Provide extract ventilation to points where emissions occur. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Material transfers	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Ensure material transfers are under containment or extract ventilation.
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimize exposure. Wear suitable gloves tested to EN374.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment break-in or maintenance. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage	Store substance within a closed system. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

2.2b. Control of consumer exposure

Product Category(ies)	Operational conditions and risk management measures
Not applicable	

3. Exposure estimation and references

Health

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated

Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

4. Guidance for Downstream User to check compliance with the Exposure scenario

Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for carcinogenic effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Risk Management Measures are based on qualitative risk characterization.

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

ES08007

Version 1.0

Trade name / designation Heavy Fuel Oil

1. Exposure scenario

Use as a fuel, Industrial.

Use Descriptor

Sector of use

SU3 - Industrial Manufacturing (all)

Process category

PROC1 - Use in closed process, no likelihood of exposure

PROC2 - Use in closed, continuous process with occasional controlled exposure

PROC3 - Use in closed batch process (synthesis or formulation)

PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC16 - Using material as fuel sources, limited exposure to unburned product to be expected

Environmental Release Category

ERC7 - Industrial use of substances in closed systems

Specific Environmental Release Category

ESVOC SpERC 7.12a.v1.

Processes, tasks, activities covered

Covers the use as a fuel (or fuel additives and additive components) within closed or contained systems, including incidental exposures during activities associated with its transfer, use, equipment maintenance and handling of waste.

2. Operational conditions and risk management measures

2.1. Control of environmental exposure

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Fraction of EU tonnage used in region: 0.1

Regional use tonnage (tonnes/year): 1.1E+7

Fraction of Regional tonnage used locally: 1.4E-1

Annual site tonnage (tonnes/year): 1.5E+6

Maximum daily site tonnage (kg/day): 5.0E+6

Frequency and duration of use

Continuous release
Emission Days (days/year): 300

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Release fraction to air from process (initial release prior to RMM): 7.0E-4

Release fraction to wastewater from process (initial release prior to RMM): 4.4E-7

Release fraction to soil from process (initial release prior to RMM): 0

Technical conditions and measures at process level to prevent release

Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Risk from environmental exposure is driven by freshwater sediment

Onsite wastewater treatment required

Prevent discharge of undissolved substance to or recover from onsite wastewater

Treat air emission to provide a typical removal efficiency of (%): 95

Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 87.7

If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%): ≥ 0

Organizational measures to prevent/limit release from the site

Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Estimated substance removal from wastewater via domestic sewage treatment (%): 88.8

Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%): 88.8

Maximum allowable site tonnage (MSafe) (kg/d): 5.2E+6

Assumed domestic sewage treatment plant flow (m3/d): 2000

Conditions and measures related to external treatment of waste for disposal

Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment.

Conditions and measures related to external recovery of waste

This substance is consumed during use and no waste of the substance is generated.

Remarks

Additional information on the basis for the allocation of the identified OCs (operating conditions) and RMMs (Risk Management Measures) is contained in Petrorisk file

2.2. Control of exposure - Workers / Consumers

Product characteristics**Physical State**

Liquid, vapor pressure < 0.5 kPa at STP

Concentration of substance in product

Covers percentage substance in the product up to 100 % (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting exposure

Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.

2.2a. Control of worker exposure

Contributing Scenarios	Operational conditions and risk management measures
General measures (carcinogens)	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimize exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorized persons; provide specific activity training to operators to minimize exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure. Avoid carrying out operation for more than 4 hours. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
General exposures (closed systems) Product sampling	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure. Avoid carrying out operation for more than 1 hour. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Bulk closed unloading Outdoor	Transfer via enclosed lines. Avoid carrying out activities involving exposure for more than 4 hours. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Operation of solids filtering equipment	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Drum/batch transfers	Ensure material transfers are under containment or extract ventilation. or. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 1 hour. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Use as a fuel (closed systems)	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment break-in or maintenance. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Bulk product storage	Store substance within a closed system. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

2.2b. Control of consumer exposure

Product Category(ies)	Operational conditions and risk management measures
Not applicable	

3. Exposure estimation and references

Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

4. Guidance for Downstream User to check compliance with the Exposure scenario

Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for carcinogenic effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Risk Management Measures are based on qualitative risk characterization.

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

ES08008

Version 1.0

Trade name / designation Heavy Fuel Oil

1. Exposure scenario

Use as a fuel, Professional.

Use Descriptor

Sector of use

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process category

PROC1 - Use in closed process, no likelihood of exposure

PROC2 - Use in closed, continuous process with occasional controlled exposure

PROC3 - Use in closed batch process (synthesis or formulation)

PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC16 - Using material as fuel sources, limited exposure to unburned product to be expected

Environmental Release Category

ERC9a - Wide dispersive indoor use of substances in closed systems

ERC9b - Wide dispersive outdoor use of substances in closed systems

Specific Environmental Release Category

ESVOC SpERC 9.12b.v1.

Processes, tasks, activities covered

Covers the use as a fuel (or fuel additives and additive components) within closed or contained systems, including incidental exposures during activities associated with its transfer, use, equipment maintenance and handling of waste.

2. Operational conditions and risk management measures

2.1. Control of environmental exposure

Product characteristics

Substance is complex UVCB. Predominantly hydrophobic.

Fraction of EU tonnage used in region: 0.1

Regional use tonnage (tonnes/year): 3.3E+5

Fraction of Regional tonnage used locally: 5.0E-4

Annual site tonnage (tonnes/year): 1.7E+2

Maximum daily site tonnage (kg/day): 4.6E+2

Frequency and duration of use Continuous release

Emission Days (days/year): 365

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Release fraction to air from process (initial release prior to RMM): 1.0E-4

Release fraction to wastewater from process (initial release prior to RMM): 0.00001

Release fraction to soil from process (initial release prior to RMM): 0.00001

Technical conditions and measures at process level to prevent release

Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Risk from environmental exposure is driven by humans via indirect exposure

No wastewater treatment required

Treat air emission to provide a typical removal efficiency of (%): N/A

Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%): ≥ 0

If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%): ≥ 0

Organizational measures to prevent/limit release from the site

Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Estimated substance removal from wastewater via domestic sewage treatment (%): 88.8

Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%): 88.8

Maximum allowable site tonnage (MSafe) (kg/d): 2.3E+3

Assumed domestic sewage treatment plant flow (m3/d): 2000

Conditions and measures related to external treatment of waste for disposal

Combustion emissions limited by required exhaust emission controls. Combustion emissions considered in regional exposure assessment.

Conditions and measures related to external recovery of waste

This substance is consumed during use and no waste of the substance is generated.

Remarks

Additional information on the basis for the allocation of the identified OCs (operating conditions) and RMMs (Risk Management Measures) is contained in Petrorisk file

2.2. Control of exposure - Workers / Consumers

Product characteristics**Physical State**

Liquid, vapor pressure < 0.5 kPa at STP

Concentration of substance in product

Covers percentage substance in the product up to 100 % (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting exposure

Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.

2.2a. Control of worker exposure

Contributing Scenarios	Operational conditions and risk management measures
General measures (carcinogens)	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimize exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorized persons; provide specific activity training to operators to minimize exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure. Avoid carrying out activities involving exposure for more than 1 hour. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
General exposures (closed systems) Product sampling	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure. Avoid carrying out activities involving exposure for more than 1 hour. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Bulk closed unloading	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Avoid carrying out activities involving exposure for more than 1 hour. or. Ensure material transfers are under containment or extract ventilation.
Refueling	Ensure material transfers are under containment or extract ventilation. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Avoid carrying out activities involving exposure for more than 1 hour.
Drum/batch transfers	Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Avoid carrying out activities involving exposure for more than 1 hour. or. Ensure material transfers are under containment or extract ventilation.
Use as a fuel (closed systems)	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Equipment cleaning and maintenance	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Drain down and flush system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately.

2.2b. Control of consumer exposure

Product Category(ies)	Operational conditions and risk management measures
Not applicable	

3. Exposure estimation and references

Health

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated

Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

4. Guidance for Downstream User to check compliance with the Exposure scenario

Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for carcinogenic effects. Available hazard data do not support the need for a DNEL to be established for other health effects. Risk Management Measures are based on qualitative risk characterization.

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).